

Construction Standards

page 1 of 1

.1 Toilet Compartments

- .1 Toilet compartments
 - .1 Shall be designed for heavy traffic, shall have superior durability, reparability and be scratch-, dent-, marking-, moisture- and impact-resistant. Use finishes that require minimal maintenance and allow easy graffiti removal; satin finish both sides.
 - .2 Design stalls size to allow adequate installation and functionality of all accessories.
- .2 Toilet partitions types
 - .1 Typical: Solid Colour Reinforced Composite (SCRC), Solid Phenolic, Solid Plastic, or Plastic Laminate, to suit budget. Acceptable products:
 - .1 Bobrick Sierra 1090
 - .2 Hadrian
 - .2 Acceptable: for non-public, limited budget projects, or to match existing: powder coated steel. Products:
 - 1 Shanahan's
- .3 Washroom partitions: Floor Mounted Overhead Braced.
- .4 Urinal partitions: Wall Hung
- .5 Each compartment to be complete with the following hardware:
 - .1 Combination coat hook/door bumper. Locate at 915mm height on inside of stall door in accessible stalls.
 - .2 Combination stop/ latch with emergency lift feature.
 - .3 Non-removable self closing hinges with emergency lift feature.
 - .4 Door d-pulls on interior and exterior of stalls for accessible compartments.
 - .5 Seat at dressing cubicles.