



.1 General

- .1 Each washroom on Campus shall be provided with the accessories listed below. In order to maintain product consistency throughout the campus, alternates are not acceptable for these products.
- .2 All necessary surface/assembly preparation shall be described in the drawings and specifications.
- .3 Coordinate with FMGT for work to be included within the project and alternatively any items to be provided by the University.

.2 Products

.1 Paper Towel Dispensers - One dispenser for every three washbasins

	Product	Description	Supplier
.1	Frost #101 9.5"h x 10.5"w x 6.75"d	Single fold paper towels cabinet #101 Wheelchair accessible	Wesclean / ACME
.2	Kruger Designer 2 #9772 15.62"h x 10.5"w x 8.5"d	Roll towel cabinet	ACME
.3	KimberlyClarke Professional 12" x 16" x 9.5	Roll towel cabinet	Unisource
.4	Kimberly Clarke Model #06904 14.3"h x 8.9"w x 2.8"d	Slimfold towel dispenser	Unisource

.2 Toilet Roll Dispensers - One dispenser for each WC

.1	Kimberly Clarke JRT 52 x 33.4 x 14.6 cm	combination dispenser toilet rolls cabinet	Unisource
.2	Frost 150	1.5 Size uncovered small toilet roll holder	Wesclean / ACME

.3 Soap Dispensers - One dispenser for every two washbasins

.1	Deb – 1L 9.25"h x 5.25"w x 4.5"d	foam soap dispenser	ACME
.2	Tork #570028A 11.5"h x 4.5"w x 4.5"d	liquid soap dispenser	Bunzyl
.3	Gojo #5150-06 10.5"h x 6.25"w x 5"d	foam soap dispenser	Unisource

.4 Sanitary Napkin Disposal - One disposal for each WC in Women's washroom

.1	Rubbermaid mod #6140 12.5"w x 10.75"h x 5"d	sanitary napkin disposal	ACME
----	--	--------------------------	------

.5 Wastepaper Receptacles - Minimum one receptacle for each washroom

- .1 Base: "Rubbermaid" No. 3568 - 14.5" wide x 4.5" deep x 24" high
- .2 Top: "Rubbermaid" No. 2662 - 14.7" wide x 14.7" deep x 5" high
- .3 Colour: Gray

.6 Sanitary Napkin Dispenser - One dispenser for each Women's washroom

- .1 "G.H. Wood" No. 113047 - 12" wide x 6" deep x 27" high (approximate dimensions)



- .2 Wall mount double combination vendor
 - .3 25 cent coin dispensing
 - .4 Finish: Stainless Steel
- .7 Grab Bars** - Locate in each accessible toilet compartment:
- .1 One at 120°, 600mm (or 180°, 1200mm) and one at 180°, 450mm x 32mm dia. X min.
 - .2 1.25mm wall tubing of 304 stainless steel, 76mm dia.
 - .3 Wall flanges concealed screw attachment, flanges welded to tubular bar, provided with steel backing plates and all accessories.
 - .4 Knurl bar at area of hand grips.
 - .5 Grab bar material and anchorage to withstand downward pull of 2.2 kN.