



.1 **Cabinet and Shelving Hardware**

.1 Use only heavy duty hardware.

.2 Cabinet Locks: Schlage "CL" series

In order to maintain consistent keying throughout the campus, alternates are not acceptable for cabinet locks. Mount flush to face of cabinetry.

.1 Review locking and keying requirements with UVic.

.2 Keyway to be specified by UVic and Key Schedule to be supplied by UVic.

.3 Door locks: CL100PB (25 mm throw bolt) c/w trim collar 36-031 and slot strike 10-052.

.4 Drawer locks: CL200PB (19 mm throw bolt) c/w trim collar 36-031 and slot strike 10-052.

.5 Finish: 626 - satin chromium plated.

.6 Cylinder alignment: vertical (horizontal alignment not acceptable)

.3 Metal bolt - to be installed at the stationary door of a pair with a lockable active door.

.1 Richelieu - B 375-180, chromium or nickel finish, complete with recessed mounted slot strike installed with countersunk screws.

.4 Hinges: heavy-duty, concealed European design, min. 105° opening, self-closing operation and secure joint to resist removal of door, c/w mounting plates. Provide hinges for full overlay and twin application, as required. Finish: 626 - satin chromium. Product: Blum Modul 107°.

.5 Drawer slides: side mount, ball bearings, full extension, telescoping, trigger disconnect, chrome or zinc finish. Products (select to suit use):

.1 Accuride: 3832 series - 45 kg rating; 3640 series - 90 kg rating (storage drawers)

.2 Grant, HEG-4932 - load rating 60 kg.

.6 Latches: magnetic touch. Product: Richelieu 9783-145.

.7 Pulls: wire type D-pull 9 mm diameter, 96 mm centres, 26 mm depth, chrome satin finish. Product: Gallery 945-26D, or Richelieu 2214-175.

.8 Flush Pulls for sliding glass doors: Richelieu D010127 satin chrome.

.9 Glass for cupboard doors: 6 mm thick, clear, tempered.

.10 Door and Drawer bumpers: 5 mm diameter, neutral colours; 2 bumpers per door up to 1200 mm in door height; 3 bumpers per door over 1200 mm in door height; 2 bumpers per drawer.

.11 Adjustable shelf supports: (semi)recessed (not surface mounted) pilasters c/w seismic support clips. Products: Richelieu, Pilasters 2552G c/w clips 242762G.

.12 Grommets to suit wiring through millwork components: cable entry plug, plastic, typical, Ø72 mm, larger Ø where required. Product: Richelieu A 60.0910-90, or larger size, as required.

.6 **Hardware Schedule**

.13 Consultant shall produce the Hardware Schedule, as part of project documentation.